



UNIFLEX
FLOOR COATINGS

**TECHNICAL
DATA
SHEET**

January, 2025



UNIFLEX
FLOOR COATINGS

UNIQUARTZ

*Floor & wall covering,
interior exterior*

DESCRIPTION	UNIQUARTZ is a Ready-to-use single-component coating based on polymer, water and granite for technical and decorative coating of floors and walls indoors and outdoors.
APPLICATIONS	<p>Exterior: Pedestrian paths, Car access, Parking, Garage ramps, Courtyards, Landscaping, Pool surrounds and Beaches, Low walls, Fences, Terraces and Balconies, Steps, Porches and House Foundations, Renovation, Stadium stands, Playgrounds, Disabled access, etc.</p> <p>Interior: Halls, Corridors, Cellars, Building levels, Stairwells, Corridors, Warehouses, Toilets, Offices, Activity premises, Shops, etc</p> <p>New Constructions or Renovations: For individuals, Condominiums, Hotels, Businesses, Traders, Public spaces, etc.</p>
ADVANTAGES	<ul style="list-style-type: none">▪ Ready-to-use single-component product▪ Exceptional adhesion, does not require primer▪ Drying: approximately 1 hour depending on application conditions▪ More than 20 shades available on color chart and possibility of tinting on request▪ Abrasion resistant▪ Resistant to freezing and thawing▪ UV resistant (does not yellow)▪ Resistant to salt, oil, gasoline▪ Non-slip▪ Elasticity 100%▪ Subsequent connections not visible▪ Ecological product without odor (very low VOC rate)▪ Application between 2 and 30°C▪ Product warranty: 15 years▪ Shelf life of the product in pot: +10 years
TECHNICAL DATA	<p>Packaging: 25 KG PAIL or 18.8L (5 US GALLON)</p> <p>APPLICATION: ±2.3 kg/m² for 3mm thickness applied in 2 layers, i.e. approximately 11m² per pot</p> <p>USE: Outdoors and indoors on horizontal and vertical supports. For perfect homogeneity, the product must be mixed with the appropriate tool approximately 1 minute before use. The unconsumed product can be kept for 10 years in its original hermetically sealed pot and stored in a dry place at a temperature between 5 and 30 °C.</p> <p>SUPPORTS: This product can be applied to all concrete, cement, tile, wood, metal supports, etc. The support must be sound and completely free of any dirt; dust, oil, grease, glue, etc. A damaged support can be repaired beforehand with a polymer-based concrete. A maximum humidity level of 30% is tolerated on concrete supports.</p>
HEALTH AND SAFETY	<p>In case of contact with eyes or skin, rinse thoroughly with clean water. In case of lasting discomfort, consult a doctor. Composed mainly of water, this product does not contain any toxic or dangerous ingredients. However, when using it, it is strongly recommended to wear protective glasses and gloves.</p> <p>*Consult the material safety data sheet for further information.*</p>
IMPORTANT NOTICE	<p>The technical information contained in this document is purely indicative and formulated following tests carried out by the company UNIFLEX FLOOR COATINGS and its experience in the application of the product. It is up to each user to check and test the veracity of this information before each application. The company UNIFLEX FLOOR COATINGS assumes no responsibility for the use of the product.</p>